

AREC CI-218




AREC CI-218 Full HD Fixed Network Camera offers 1080p Full HD resolution with excellent image quality. Equipped with an 18x optical zoom lens, AREC CI-218 allows users to shoot close-up view of the presenter and adjust the field of view in accordance with different indoor environments.

Main Features

Fully Enjoy the High Definition Video

With high performance H.264 compression technology, AREC CI-218 Network Camera provides Full HD, crystal-clear video recording with a minimum of bandwidth consumption, reducing the file size effectively.



Get Better Control with Auto Focus

With auto focus feature, AREC CI-218 fixed indoor network cameras enable users to control zoom in and zoom out remotely from the web-based backstage or AREC Online Director* without the need of manual focus adjustment.

* Control through AREC Online Director, CI series cameras should be connected with AREC Media Station in advance.



Auto Focus

Advanced WDR and Noise Reduction Technology

With WDR Enhancement technology, AREC CI-218 allows users to shoot clear video images in extremely bright and dark environments. Moreover, with digital noise reduction technology, AREC CI-218 can automatically remove the noise on the video when lighting conditions is poor, providing crystal-clear video performance.



Simplicity Style for Diverse Indoor Environment

Adopting modern silver and white color, AREC CI-218's simplicity style allows users to install the camera in accordance with diverse indoor environment, such as classrooms, meeting rooms or enterprise training rooms. The simple and light color also can reduce the nervousness of photographed people.



Fit for Any Indoor Environment

Specifications

| Model Name | AREC CI-218 Full HD Network Camera | |
|-----------------------|--|--|
| Model Name | | |
| Camera | | |
| Image Sensor | 1/2.8" progressive CMOS | |
| Minimum Illumination | 0.03 Lux @ F 1.6 (color); 0.003 Lux @ F 1.6 (B/W) | |
| White Balance | Manual / ATW / Auto | |
| Shutter Speed | 1 - 1/10000 sec. | |
| Lens (Auto Focus) | 18x optical zoom | |
| Focal Length | 4.7 – 84.6 mm (18x) | |
| F Number | F1.6 (wide); F2.8 (tele) | |
| Filed of View | 63.4° (wide) – 4.5° (tele) | |
| Video | | |
| Video Compression | MJPEG / H.264 (MPEG-4 Part 10/AVC) Baseline / Main Profile / High Profile | |
| Video Resolution | H.264: Full HD 1080P / HD 720P / XGA / SVGA / D1 / VGA / CIF MJPEG: Full HD 1080p / HD 720p / XGA / SVGA / D1 / VGA / CIF | |
| Image Auto Adjustment | BLC / auto white balance / 3D noise reduction / WDR | |
| Image Setting | Brightness / exposure / sharpness / contrast / saturation / hue / ICR / digital zoom | |
| Privacy Mask Type | Yes, color | |
| Audio | | |
| Two-Way Audio | Yes | |
| Audio Compression | G.711/ G.726 | |
| Network | | |
| Network Interface | RJ-45, 10/100/1000 Mbps Ethernet (Giga Ethernet) | |
| Support Dual Streams | Yes | |
| Protocol | IPv4 / v6, TCP / IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS | |
| Security | HTTPS / IP filter / IEEE 802.1x | |

| Mechanical & Interface | | |
|------------------------|---|--|
| LED Indicator | Power / Link / ACT | |
| Auto Iris | DC drive | |
| Alarm | 4-pin terminal block | |
| Power | 3-pin terminal block | |
| Ethernet | RJ-45 | |
| Analog Video | 1.0 Vp-p / 75Ω, BNC | |
| RS-485 | D+, D- | |
| Audio | Line in / Line Out | |
| General | | |
| Operating Temperature | -10°C ~ 50°C (14°F ~ 122°F) | |
| Humidity | 10% - 90% RF | |
| Supported Web Brower | Internet Explorer (6.0+) / Chrome / Firefox / Safari | |
| Dimension (L x W x H) | 183.4 x 75.2 x 52.4 mm | |
| Weight | 450g (1 lb) | |
| Power Source | 12V DC / 24V AC / PoE | |
| Power Consumption | 9W | |
| Certification | CE / FCC / RoHS | |
| Language | English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese | |

Product Appearance & Connectors

Appearance

183.48 195.33 Length Units:mm

■ Connectors

