

AREC CI-303

Network Camera



3x Wide-Angle Optical Zoom Lens



Main Features

Fully Enjoy the High Definition Video

With high performance H.264 compression technology, AREC CI-303 Network Camera provides Full HD, crystal-clear video recording with a minimum of bandwidth consumption, reducing the file size effectively.





Full HD Resolution

Get Better Control with Auto Focus

With auto focus feature, AREC CI-303 fixed indoor network cameras enable users to control zoom in and zoom out remotely from the web-based backstage or AREC Online Director* without the need of manual focus adjustment.

* Control through AREC Online Director, CI series cameras should be connected with AREC Media Station in advance.



Auto Focus

Advanced WDR and Noise Reduction Technology

With WDR Enhancement technology, AREC CI-303 allows users to shoot clear video images in extremely bright and dark environments. Moreover, with digital noise reduction technology, AREC CI-303 can automatically remove the noise on the video when lighting conditions is poor, providing crystal-clear video performance.



WDR Off WDR On

Simplicity Style for Diverse Indoor Environment

Adopting modern silver and white color, AREC CI-303's simplicity style allows users to install the camera in accordance with diverse indoor environment, such as classrooms, meeting rooms or enterprise training rooms. The simple and light color also can reduce the nervousness of photographed people.



Fit for Any Indoor Environment


Specifications

Model Name	AREC CI-303 Full HD Network Camera	
Camera		
Image Sensor	1/3" Progressive CMOS	
Minimum Illumination	0.1 Lux @ F 1.2 (color); 0.01 Lux @ F 1.2 (B/W)	
White Balance	Manual / ATW / Auto / One Push	
Shutter Speed	1 - 1/10000 sec.	
Lens (Auto Focus)	3x wide-angle optical zoom	
Focal Length	3.0 – 9.0 mm (3x)	
F Number	F1.2 (wide); F1.7 (tele)	
Filed of View	109° (wide) – 33° (tele)	
Video		
Video Compression	MJPEG / H.264 (MPEG-4 Part 10/AVC) Baseline / Main Profile / High Profile	
Video Resolution	H.264: 3M (2304x1296) / Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF MJPEG: Full HD 1080p / HD 720p / XGA / SVGA / D1 / VGA/ CIF	
Image Auto Adjustment	BLC / auto white balance / 3D noise reduction / WDR / HDR (Multiple Shutter Exposure)	
Image Setting	Brightness / exposure / sharpness / contrast / saturation / hue / ICR / digital zoom	
Privacy Mask Type	Yes, color	
Audio		
Two-Way Audio	Yes	
Audio Compression	G.711 / G.726 / AAC / LPCM	
Network		
Network Interface	RJ-45, 10/100 Mbps Ethernet	
Support Dual Streams	Yes	
Protocol	IPv4 / v6, TCP / IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS	
Security	HTTPS / IP filter / IEEE 802.1x	

Mechanical & Interface		
LED Indicator	Power / Link / ACT	
Auto Iris	DC drive	
Alarm	4 of 9 Pin Terminal Block, Pitch 3.5 mm	
Power	DC jack	
Ethernet	RJ-45	
Analog Video	1.0 Vp-p / 75Ω, BNC	
RS-485	D+, D-	
Audio	Stereo Phone Jack, Ø 3.5mm	
General		
Operating Temperature	-10°C ~ 50°C (14°F - 122°F)	
Humidity	10% - 90% RF	
Supported Web Brower	Internet Explorer (7.0+) / Firefox / Safari	
Dimension (L x W x H)	165 x 75.2 x 52.4 mm	
Weight	360g (0.8 lb)	
Power Source	12V DC / 24V AC / PoE	
Power Consumption	4.65W	
Certification	CE / FCC / RoHS	
Language	English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese	

Product Appearance & Connectors

Appearance



■ Connectors

